


Electrical Specifications:

Type	WRL1206				WRL2512			
Metric Size	3216				6432			
Power Rating	1/2W (0.50W)				1/3W (0.33W)	1/2W (0.50W)	1.0W	1.0W
Resistance Range	0.5mΩ	1mΩ~4mΩ	5mΩ~9mΩ	10mΩ~100mΩ	0.5mΩ	1mΩ~2mΩ	3mΩ~4mΩ	5mΩ~100mΩ
TCR ppm/°C	±100	±75	±50	±30	±100	±75	±50	±30
Resistance Tolerance % (code)	±1%(F)	±0.5%(D), ±1%(F)		±0.3%(C)±0.5%(D)	±0.5%(D), ±1%(F)			
Operating Temp. Range	-55°C~+155°C							
Packaging (code)	5,000pcs/reel (-T5)				4,000pcs/reel (-T4)			


Power Derating Curve:**Reliability Specifications:**

Test	Procedure	Specification
Short Time Over Load IEC60115-1 4.13	$P = 2.5P_r$; $T = 25 \pm 2^\circ\text{C}$, $t = 5\text{sec.}$	±1.0%
High Temp. Exposure IEC60115-1 4.25	$T = +170 \pm 2^\circ\text{C}$; $t = 1000\text{h}$	±1.0%
Low Temp. Storage IEC60115-1 4.25	$T = -55 \pm 2^\circ\text{C}$; $t = 1000\text{h}$	±1.0%
Moisture Load Life (60°C, 95%RH) IEC60115-1 4.25	$V_{\text{test}} = V_{\text{max}}$; $T = 60 \pm 2^\circ\text{C}$; $\text{RH} = 95\%$; $t = 90\text{min ON, 30min OFF, 1000h}$	±2.0%
Thermal Shock IEC60115-1 4.19	$[-55^\circ\text{C } 30\text{min.} \rightarrow \text{R.T. } 3\text{min.} \rightarrow +150^\circ\text{C } 30\text{min.} \rightarrow \text{R.T. } 3\text{min.}]$, 100 Cycles	±1.0%
Load Life at 70°C IEC60115-1 4.25	$V_{\text{test}} = V_{\text{max}}$; $T = 70 \pm 2^\circ\text{C}$; $t = 90\text{min ON, 30min OFF, 1000h}$	±2%
Solderability IEC60115-1 4.17	Dip into solder at $T = 245 \pm 5^\circ\text{C}$, $t = 3 \pm 0.5\text{sec.}$	The covered area >95%
Resistance to Solder Heat IEC60115-1 4.18	Through Reflow $T = 275 \pm 5^\circ\text{C}$, $t = 20 \pm 1\text{sec.}$	±1.0%
Mechanical Shock IEC60115-1 4.21	$a = 100\text{G}$, $t = 11\text{ms}$, 5 times shock	±1.0%
Substrate Bending IEC60115-1 4.33	Span between fulcrums : 90mm Bend Width : 2mm ; Test board : Glass-Epoxy Board Thickness = 1.6mm	±1.0%


AEC-Q200 Test Requirements (Table 7):

AEC Test #	Test Name	AEC-Q200 Test Requirements	Specification
3	High Temp. Exposure (Storage) MIL-STD-202, Method 108	Test Temp 125 \pm 3°C Test Period: 1,000 hours No Electrical Load	\pm 1.0%
4	Temp. Cycling (Thermal Shock) JESD22 Method JA-104	Repeat 1,000 cycles as follows: -55 \pm 3°C for 30 minutes 125 \pm 3°C for 30 minutes Transition time of 1 minute max	\pm 1.0%
7	Biased Humidity MIL-STD-202, Method 103	Test conditions: 85°C and 85% RH 10% of rated power Test Period 1,000 hours	\pm 1.0%
8	Load Life (Operational Life) MIL-STD-202, Method 108	Test Temperature: 125 \pm 3°C Applied voltage: rated power (derated Power will be required if temp exceeds the derating point of part) Test Period: 1,000 hours (condition D)	\pm 1.0%
12	Resistance to Solvents MIL-STD-202, Method 215	3 minute soak 2-3 ounce force 10 strokes/repetition 3 repetitions	No damage
13	Mechanical Shock MIL-STD-202, Method 213	Force: 100G peak Test duration: 6 ms Half-sine waveform Velocity: 12.3ft/sec	\pm 1.0%
14	Vibration MIL-STD-202, Method 204	Frequency: 10-2,000 Hz Acceleration: 5G Test duration: 20 minutes, 12 cycles	\pm 1.0%
15	Resistance to soldering heat MIL-STD-202, Method 210	Condition B (Solder dip, no pre-heat) 260 \pm 5°C	\pm 1.0%
17	ESD AEC-Q200-002	HBM, 100pF, 1.5k ohms Repetition: 5 times	\pm 1.0%
18	Solderability J-STD-002	Non-activated flux dip: 5-10 seconds SAC solder dip: 2 \pm 0.5 seconds at 245 \pm 5°C	95% coverage
20	Flammability UL-94	V-0 or V-1 are acceptable Electrical test not required	Provide certificate
21	Board Flex AEC-Q200-005	90 mm span between fulcrums 2 mm bend 60 seconds minimum holding time	\pm 1.0%
22	Terminal Strength (SMD) AEC-Q200-006	Force of 17.7 N 60 seconds	\pm 1.0%
24	Flame Retardance AEC-Q200-001	Mounted parts subjected to voltages from 9.0 to 32 VDC (current clamped up to 500A) in 1.0 VDC increments. Voltage applied for 1hour minimum or until failure occurs	Must meet AEC-Q200 requirements

Plastic Taping Dimensions:


 <p style="text-align: right;">All dimensions in mm.</p>												
Type	W	P0	P	P2	A0	B0	D0	F	E	T	T1	K0
WRL1206	8.00 \pm 0.30	4.00 \pm 0.10	4.00 \pm 0.10	2.00 \pm 0.10	1.90 \pm 0.20	3.50 \pm 0.20	1.50 \pm 0.10	3.50 \pm 0.10	1.75 \pm 0.10	0.20 \pm 0.10	Max 0.10	0.85 \pm 0.20
WRL2512	12.0 \pm 0.30	4.00 \pm 0.10	4.00 \pm 0.10	2.00 \pm 0.10	3.40 \pm 0.20	6.75 \pm 0.20	1.50 \pm 0.10	5.50 \pm 0.10	1.75 \pm 0.10	0.25 \pm 0.10	Max 0.10	0.81 \pm 0.20

Reel Dimensions:


	Type	A	N	W1
	WRL1206	178 ±5.00	60.0 ±2.00	9.00 ±1.00
	WRL2512	178 ±5.00	60.0 ±2.00	13.0 ±1.00

All dimensions in mm.

Recommended Land Pattern:

	Type	P	W1	W2	D
	WRL1206	1.20	1.10	0.30	1.80
	WRL2512	3.10	1.40	0.70	2.00

All dimensions in mm.

Recommended Soldering Profile:**Storage Conditions:****Environmental Conditions:**

Products should be stored under the following environmental conditions:

- Temperature: +5 to +40°C
- Humidity: 45 to 85% relative humidity
- Do not keep products in environments where they may be subject to particulate contamination or harmful gases such as sulfuric acid or hydrogen chloride as it may cause oxidization on electrodes, resulting in poor solderability.
- Products should be stored in a space that does not expose it to high temperatures, vibration, or direct sunlight.
- Products should be stored in the original airtight packaging until use.